


23x Mini Indoor Speed Dome Camera



Main Features

- ⇒ 1/4" High Quality Image Sensor
- ⇒ High Resolution of 540TVL
- ⇒ Min. Illumination of 0.5 Lux/F1.6
- ⇒ Powerful 23x Optical Zoom
- ⇒ Day/Night (ICR), 2D-DNR, Auto iris, Auto focus, AWB, AGC, BLC
- ⇒ Max 300°/s pan speed, 360° continuous pan rotation
- ⇒ Up to 255 presets, 5 auto scan, 8 tour, 5 pattern
- ⇒ Built-in 2/1 alarm I/O



Feature	Specification
Image Sensor	1/4" High Quality Image Sensor
Pixels	640(H) × 480(V)
Resolution	540TVL
Min. Illumination	0.5 Lux/F1.6
S/N Ratio	More than 50dB
Electronic Shutter	1/50(60)s ~1/100,000s
Zoom Optical	23x
Lens	3.9 mm~89.7mm
Focus Mode	Auto / Manual
White Balance (AWB)	Auto, ATW, Indoor, Outdoor, Manual
Gain Control (AGC)	Auto / Manual
Back Light Comp.	BLC
Privacy Masking	Up to 24 areas
Angle of View	61.68° ~ 3.06°
Day & Night (ICR)	Auto(ICR) / Color / B/W
Close Focus Distance	100mm~1000mm
Special Functions	Day/Night (ICR), 2D-DNR, Auto iris
Pan Range	0° ~ 360° endless
Pan Speed	0.1° ~ 250°/s
Tilt Range	0° ~ 90°, auto flip 180°
Tilt Speed	0.1° ~150°/s
Number of Presets	255
Preset Speed	Pan: 300°/s; Tilt:200°/s
Idle Motion	Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period
Power up Action	Auto restore to previous PTZ and lens status after power failure
Alarm	2/1 channel In/Out

Feature	Specification
Time Task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Communication	RS485
Sync. System	Interlacing
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
Power Supply	AC24V/1.5A (±10%), DC12V optional
Power Consumption	12W
Dimensions	Φ170mm×155mm
Weight	1.5KG
Operating Temp	-10°C ~ 50°C / Less than 90% RH