

KX-VDW200SX



Camera

- *Image Sensor*
 - 1/2.8" CMOS, 2MP
- *Focal*
 - f=3.9mm-46.8mm
- *Iris*
 - F1.6-F2.8
- *Zoom*
 - Optical:12X, Digital:12X
- *FOV*
 - Horizontal 72.5°-6.3
- *Focus*
 - Auto, Manual, PTZ Push, One Push
- *Shutter Speed*
 - 1/1~1/10,000s
- *AGC*
 - Auto, Manual
- *White Balance*
 - Auto, Indoor, Outdoor, One Push, Manual, AutoTrack, Color Temp
- *Exposure*
 - Auto, Manual, Shutter Priority, Iris Priority
- *SN Ratio*
 - ≥ 50dB
- *BLC*
 - Yes

Full View Camera

- *Image Sensor*
 - 1/2.5" 4K CMOS Sensor, 8.57MP
- *Lens*
 - 2.8mm focus, 4X digital zoom
- *FOV*
 - 98°
- *DNR*
 - 2D/3D
- *Video Adjustment*
 - Support EPTZ

PTZ

- *Pan*
 - -90°~+90°, 0.1°~100°/s
- *Tilt*
 - -30°~+90°, 0.1°~80°/s
- *Preset Number*
 - 64

Network

- *Max Image Size*
 - 1920×1080@60fps
- *Video Compression*
 - H.264/H.265/MJPEG
- *Audio Compression*
 - AAC
- *Protocol*
 - RTSP, RTMP, RTP, TCP, UDP, ONVIF
- *Multi-Stream*
 - Support 1×close-upview, 1×fullview, 1×switching

Interface

- *SDI*
 - 1×3G-SDI, VideoFormat: 1080P60/50/30/25, 720P60/50
- *HDMI*
 - 1×HDMI, VideoFormat: SameasSDI
- *USB*
 - 1×USB2.0 , supportUVC/UAC
- *Audio Input*
 - 2×3.5mm LINEIN, including one channel echo cancellation reference audio input
- *Network Interface*
 - 1x10M/100M RJ45

General

- *Control Protocol*
 - VISCA
- *Address*
 - 44348
- *Power Supply*
 - DC12V
- *Power Consumption*
 - <20W
- *Working Temperature*
 - 0°C~+40°C
- *Storage Temperature*
 - -20°C~+60°C
- *Dimension (L×W×H)*
 - 245mm×145mm×165mm
- *Weight*
 - < 2KG